

SILENT CANOPY SINGLE-PHASE DIESEL GENERATING SET

YANMAR 6 kVA / 4.8 kW
/ SILENT SITE STAGE V

50 Hz · 220–230 V · single phase
Wheel-mounted silent site set · Model YM6S

RATED OUTPUT	VOLTAGE	CURRENT @ 230 V	ENGINE
6 kVA 4.8 kW _e	230 / 110 V site sockets	26 A single phase	L100V Yanmar 0.44 L · 1 cyl



A compact wheel-mounted silent site generating set built around the Stage V Yanmar L100V air-cooled diesel and a Mecc Alte S20W-95 single-phase alternator. Rated 6 kVA / 4.8 kW at 50 Hz for light-duty rental, construction, events and mobile use. Dual-voltage site sockets (110 V and 230 V), Deep Sea 3110 auto-start, bunded 25 litre base tank and a powder-coated acoustic enclosure at typically 68 dB(A) @ 7 m.

RATINGS & ELECTRICAL OUTPUT — 50 HZ, SINGLE-PHASE, 2-WIRE

Parameter	Rated	Site duty	110 V	230 V	Notes
Apparent power	6 kVA	6 kVA	—	—	Site / rental
Active power (0.8 pf)	4.8 kW _e	4.8 kW _e	—	—	Net electrical
Line current	26 A	26 A	—	26 A	Single phase 230 V
Sockets	—	—	2×16 + 1×32 A	1×16 + 1×32 A	IEC 60309
Frequency / speed	50 Hz	50 Hz	—	—	3,000 r/min
Voltage regulation	±1 %	±1 %	—	—	Steady state, AVR
Power factor	0.8 lag	0.8 lag	—	—	As rated
Circuit breaker	25 A	25 A	—	—	ABB 2-pole MCB

RATING DEFINITIONS

PRIME POWER (PRP) — ISO 8528-1 Unlimited running hours in a variable-load application in place of a mains supply. Average load factor over 24 hours not to exceed 70% of the PRP rating. A 10% overload is available for 1 hour in any 12 hours of operation.	STANDBY / EMERGENCY (ESP) — ISO 8528-1 Available under variable load in the event of a utility outage. No overload capability is permitted on the ESP rating. Typical annual utilisation is limited; intended for automatic mains-failure duty, not continuous baseload.
---	--

TYPICAL APPLICATIONS

Homes, farms & rural Domestic standby, workshops, grain stores, dairies, pumping and remote sites with limited grid capacity.	Commercial buildings Offices, retail, hotels, data rooms and mixed-use sites with automatic mains-failure duty.
Healthcare & care Clinics, care homes and small medical / support services needing a tested standby source.	Construction & hire Canopied prime or standby power for compounds, events and temporary works.
Retail & hospitality Shops, pubs, restaurants and small commercial premises on single-phase supplies.	Utilities & infrastructure Pumping stations, comms, water treatment and critical plant rooms.

SITE / RENTAL CONFIGURATION

This data sheet covers the SILENT SITE generating set for rental, construction, events and mobile use. It is a 3,000 r/min air-cooled Stage V package with dual-voltage site sockets, not a 1,500 r/min house standby set. Rated output is 6 kVA / 4.8 kW at 0.8 pf, 50 Hz. Auto-start is via the Deep Sea 3110. A bunded 25 litre base tank, trolley frame with handles and an internal silencer are standard.

ENGINE — YANMAR L100V STAGE V

Manufacturer	Yanmar (Japan)	Gross power (3000)	6.3 kWm / 8.5 hp
Model	L100V	Max power (3600)	6.8 kWm / 9.3 hp
Configuration	1 cylinder, vertical	Set engine power	5.7 kWm
Cycle / combustion	4-stroke, direct injection	Emissions	EU Stage V
Aspiration	Naturally aspirated	Cooling	Forced air (flywheel fan)
Bore × stroke	86 × 75 mm	Oil capacity	1.6 litres
Displacement	0.435 litres	Starting	12 V electric + cold-start aid
Compression ratio	typical L-series	Electrical system	12 V DC negative earth
Rated speed	3,000 r/min (50 Hz)	Starting	Heavy-duty lead-acid battery
Rotation (flywheel)	Anti-clockwise	Combustion air (PRP)	air-cooled — N/A
Governor	Mechanical (as built)	Exhaust flow (ESP max)	internal canopy silencer
Emissions class	Fuel-optimised	Max exhaust temp.	air-cooled L-series

FUEL CONSUMPTION — 3,000 R/MIN, TYPICAL PUBLISHED DATA

Load point	g/kWh	Litres / hour	Approx. 8 h use	Duty reference
100 % load	—	1.2 L/h	≈ 21 h	Published 100 %
75 % load	—	0.8 L/h	≈ 31 h	Typical site load
50 % load	—	≈ 0.6 L/h	≈ 42 h	Light load
Tank capacity	—	25 L bunded	—	Base-mounted
Autonomy @ 75 %	—	≈ 31 h	—	From 25 L tank

Fuel figures are engine manufacturer data at 3,000 r/min on distillate diesel to the relevant BS / EN specification, and will vary with site altitude, ambient temperature, fuel quality, load profile and installation. The standard base tank is an insulated bunded 8-hour tank with contents gauge, typically sized around 75 % prime load. Bulk tanks, bunded day tanks and automatic fuel-transfer systems are available.

ALTERNATOR — MECC ALTE S20W-95

Manufacturer	Mecc Alte	Continuous rating 40 °C	6 kVA / 4.8 kW class
Model	S20W-95	Frequency / speed	50 Hz / 3,000 r/min
Type	Brushless, 4-pole, self-excited	Voltage range	220 / 230 V single phase
Winding	Single-phase, 4-wire capable	THD (no-load, typ.)	< 2.5 – 3.5 %
Bearings	Single bearing, SAE coupled	THD (linear load, typ.)	< 5 %
Insulation	Class H	Waveform THF / TIF	< 2 % / < 50
Enclosure	IP23, drip-proof, self-cooled	Overspeed	2,250 r/min
AVR (typical)	R120 / R221 (±0.5–1 %)	Altitude (std derate)	≤ 1,000 m asl

CONTROL, PROTECTION & ELECTRICAL PACKAGE

Controller	Deep Sea DSE3110	Circuit breaker	ABB 25 A 2-pole MCB
Function	Autostart + AMF	Current transformers	Fitted as standard
Display	Back-lit LCD + LED alarms	Emergency stop	Set-mounted E-stop
Sensing	1-ph generator & 1-ph mains	Engine protection	HET, over/under speed
Current	Generator / load CTs	Electrical protection	V, Hz, I, battery
Modes	Stop / Manual / Auto / Test	Remote start	Input available
Event log	10 events (configurable)	Outputs	Fuel, crank, configurable
PC software	DSE Configuration Suite	Control voltage	12 V DC

DSE3110: compact auto-start controller with generator voltage and frequency monitoring, oil-pressure and high-temperature protection, hours-run and configurable start. Suited to site and rental auto-start. Configured by front panel or PC.

STANDARD SPECIFICATION – SILENT CANOPY SET

- Yanmar L100V Stage V air-cooled single-cylinder diesel, mechanical governor, electric start
- Air, fuel and lubricating-oil filters; industrial exhaust silencer and flexible bellows
- Inboard anti-vibration mounts (AVMs) between engine/alternator and fabricated steel baseframe
- Mecc Alte S20W-95 single-phase 2-pole alternator, Class H, IP23, AVR regulated
- Deep Sea 3110 auto-start controller with protection and hours-run
- ABB 25 A two-pole MCB and set-mounted emergency stop
- 12 V DC control system and heavy-duty lead-acid starting battery
- Bunded 25 litre base-mounted fuel tank with contents gauge
- High engine-temperature and over / under-speed protection
- Works test to ISO 8528 with test certificate issued with the set
- PRIME BUILD: engine glow plugs / cold-start aid for reliable starting on variable-load prime sites
- STANDBY BUILD: mains-powered engine coolant heater and mains battery charger so the set remains warm and the battery charged while on standby
- Powder-coated acoustic enclosure with foam lining and internal silencer
- Shot-blasted baseframe with four-coat paint system and forklift / sling handling points
- Operation and maintenance documentation pack
- UK assembly and pre-delivery inspection before despatch
- Free mainland UK delivery on the YM6S silent site set (offloading by others unless specified)

OPTIONAL EXTRAS & SYSTEM UPGRADES

ACOUSTIC / SITE

Super-silent upgrade; extra residential silencers; attenuation packs; plant-room treatment; closer-neighbour kits.

FUEL

Bulk bunded tanks; automatic fuel transfer; polishing; water-in-fuel alarms; extended-run base tanks; HVO compatibility advice.

MONITORING

Remote monitoring & control — fuel, performance, alarms and start/stop from off-site; SMS / cloud options.

HYBRID / OFF-GRID

Battery storage, UPS and solar-hybrid packages to cut run hours and fuel on prime or remote sites.

ELECTRICAL

4-pole MCCB; motorised breaker; AMF / ATS panel; synch / load-share (DSE86xx class); earth-fault; dual voltage; socket kits.

STARTING & HEATING

Additional battery set; battery isolator; jacket water heater upgrade; oil-sump heater; anti-condensation heater on alternator.

EMISSIONS / FUEL

Guidance on fuel-optimised operation, HVO blends and local planning / environmental constraints.

INSTALLATION KIT

Flue / extract design, flexible exhaust, wall flashings, drip-trays, cable containment, plinth design.

INSTALLATION ENVELOPE, ENVIRONMENT & COMPLIANCE

Set type	Silent site / trolley canopy	Design ambient	Tropical radiator (hot climate)
Typical L × W × H	Issued on GA drawing	Standard altitude	≤ 1,000 m (derate above)
Typical wet weight	Issued on GA drawing	Works test	ISO 8528 load test
Set weight	approx. 209 kg	Genset standard	ISO 8528
Set L×W×H	approx. 960 × 580 × 815 mm	Alternator std.	IEC 60034 / ISO 8528-3
Fuel tank	25 L bunded base tank	Engine std.	ISO 3046 / ISO 8528
Noise (canopy)	Typ. 68 dB(A) @ 7 m, 75 % load	Wiring	BS 7671 installation practice
Cooling air	Free inlet & discharge required	Handling	Fork / lift points as built

- The acoustic canopy is weather-protecting for outdoor siting but still needs free cooling-air inlet and discharge, a correct exhaust route and a level plinth. Do not enclose the canopy in an unventilated shed.
- Quoted noise is typical at 7 m in free-field conditions. Site reflections, hard standing and load will change the figure. Residential-adjacent sites can be further attenuated on request.
- Final dimensions, wet weight, tank litres, exhaust flange size and cable-entry details are confirmed on the general arrangement drawing issued with the quotation / order acknowledgement.
- Ratings are at 25 °C, 100 kPa, 30 % RH unless stated. Site derate applies for altitude, temperature and poorly ventilated rooms — GES Power Ltd will calculate this at survey.
- A 10 % overload on Prime is available for 1 hour in 12. Standby (ESP) has no overload. Do not apply ESP as a continuous rating.

Why specify GES Power Ltd

Family-run UK specialists in diesel generation. We do not just sell a skid — we size, build, deliver, install, commission and look after the set for its working life.

REASONS CLIENTS CHOOSE GES POWER LTD

1 One accountable UK partner

Supply, installation, electrical connection, commissioning and aftercare sit in one company. You are not passed between a seller, an electrician and a service agent when the set is on site.

2 Genuine branded engines, UK-assembled sets

British-assembled Yanmar, Perkins and Caterpillar powered generators from small commercial units through to 2,000 kVA industrial machines. This 6 kVA silent site set is supplied and works-tested in the UK before it leaves.

3 Right-sized, not oversold

We design the package around your actual load, starting kVA, ambient, fuel strategy and budget. That avoids wasted capital, excess fuel burn and hire-set overspend.

4 Prime and standby from one platform

The same silent set can be built for continuous / prime site duty or automatic standby. Glow plugs, coolant heaters, battery chargers, ATS and remote monitoring are selected to match how you will actually run the machine.

5 Turnkey installation nationwide

Site survey, plinth and location advice, HIAB offload and positioning, certified electrical installation to BS 7671, exhaust and extract systems, bulk fuel tanks and fuel-transfer, cable containment and making-good.

6 Commissioning that is more than a start-up

Functional testing of AMF / ATS, protection settings, load proving, customer training and a documented handover so your team know how to run, test and call for help.

7 Planned maintenance, not breakdown roulette

Prime and standby service schedules, genuine filters and parts, annual black-start / blackout tests and load-bank testing to prove the set still carries the building when the grid fails.

8 Repair, fault-finding and 24/7 support

Power cuts and failed starts do not keep office hours. Engineers operate nationwide from Chesterfield with common engine and control-system spares. Critical-site response is part of the offer, not an afterthought.

9 Life-extension and compliance support

Controller upgrades, remote monitoring, exhaust and extract redesign, fuel polishing, battery replacement, and help meeting insurer, healthcare and facilities-management test regimes.

10 Wider power systems, not just a diesel

ATS / AMF and synchronising panels, UPS, off-grid battery and solar-hybrid packages, and installation into vehicles or vessels. The generator can sit inside a larger resilience scheme.

11 Plain commercial terms

Clear quotations, free mainland UK delivery on this YM6S silent site set, and a family-run team you can actually speak to on 01246 380525. Established 2016 with more than twenty years' combined industry experience.

12 Return on the investment

Reduced downtime, fewer emergency hire invoices, lower fuel through correct sizing, and a maintained asset that holds value. The set is only half the product — the service wrap is the other half.

FULL SERVICE WRAP AVAILABLE WITH THIS GENERATING SET

Load assessment & kVA sizing

Site survey & plant-room design

Open or canopied build options

HIAB delivery & positioning

Certified electrical installation

AMF / ATS panel supply & wire-in

Exhaust, flue & extract systems

Bulk fuel tanks & transfer

Remote monitoring & telemetry

Training & documented commission

Planned service agreements

Load-bank & black-start testing

24/7 breakdown attendance

Genuine parts & service kits

Controller / ATS upgrades

Hybrid battery & off-grid packages

Talk to an engineer before you buy

Written for every type of client — facilities managers, contractors, farmers, healthcare estates and industrial engineers. If you are unsure about Prime versus Standby, open versus silent, ATS, exhaust routing or a service contract, call us. We will size the set and quote the installation as well as the machine.

01246 380525

GES Power Ltd · Unit 2 Cavendish Business Park, Chesterfield S41 9EY · Nationwide UK · Out-of-hours power-failure support